


# T16 Multi Color RGBW LED Linear Flex

T16-24V-5050-72-RGBW



Dimension

Vertical Bending

Min. Bending Diameter

Beam Angle

RGBW

One Bin

Dimmable

Submersible

Ambient Temp.

Class 3

LM-80

IK08

UV resistant

Flame Resistant

Saltwater Resistant

Solvents Resistant

Dirt Resistant

CE


RoHS

Warranty


## Technical Parameters

Electrical	
Input Voltage	24V DC
Power Consumption	17W/m
Physical	
LED Count	72 LEDs/m
Cutting Unit	6 LEDs
Cutting Unit Length	83.3mm
Minimum Bend Diameter	120mm
Output	
LED Light	Epistar SMD LED 5050
Color	RGBW(2200/3000/4000K)
Max Run Length*	
Single Feed	8M
Double Feed	16M
Beam Angle	120°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C
Temperature Ranges	
Installation	0°C to 50°C
Operating	-25°C to 50°C
Dependability	
Warranty	3 Years Warranty
IP Rating	IP68 Wet location submersible <2m

Emitting Color	Lumen Output
	Red 18lm/m
	Green 173lm/m
	Blue 41lm/m
	RGB(White) 513lm/m
	3000K 270lm/m



## Illuminance Distribution



# T16 Multi Color RGBW LED Linear Flex

## Connection

