

# SF34 Mono Color Silicone LED Linear Flex

SF34-24V-5050-84-2200K-6500K

## Specification



19.0mm  
22.0mm

**Dimension**

**Vertical Bending**

400mm

**Min. Bending Diameter**



Beam Angle	Ansi C78.377	SDCM<3	One Bin	Dimmable	Submersible
Ambient Temp.	Class 3	LM-80	IK08	UV resistant	Anti-Yellowing
Flame Resistant	Saltwater Resistant	Solvents Resistant	Dirt Resistant	Warranty	

## Technical Parameters


Electrical	
Input Voltage	24V DC
Power Consumption	15W/m
Physical	
LED Count	84 LEDs/m
Cutting Unit	7 LEDs
Cutting Unit Length	83.3 mm
Minimum Bend Diameter	120mm
Output	
LED Light	Epistar SMD LED 5050
CRI	>80, >90
Max Run Length*	
Single Feed	8 M
Double Feed	16 M
Beam Angle	120°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C
Temperature Ranges	
Installation	0°C to 50°C
Operating	-40°C to 55°C
Dependability	
Warranty	5 Years Warranty
IP Rating	IP68 Wet location submersible <2m

Optional Color	
	2200K(2238±102K)
	2700K(2725±145K)
	3000K(3045±175K)
	3500K(3465±245K)
	4000K(3985±275K)
	4500K(4503±243K)
	5000K(5029±283K)
	6500K(6532±510K)
	Green(520-530nm)
	Blue (455-465nm)
	Lemon Yellow(570-580nm)
	Pink(610-620nm)

## Illuminance Distribution



## White Color Charts



# SF34 Mono Color Silicone LED Linear Flex

## Connection

